BM20S Bulk Material Delivery Hose



Construction:

Tube: Black SBR/NR Blend. Abrasion Resistant .

Reinforcement: High Tensile Textile Cords.

Cover: Black IR/BR Blend; Abrasion and Ozone

Resistant.

Temperature Range: -35°C To +85°C.

Typical Application: Bulk Material Delivery. Specially designed for heavy duty Barite and Cement delivery to offshore platforms.

Branding:

Barite Service:

Ontinental → ContiTech BM20S BULK MATERIAL DELIVERY WP 20 BAR

Black text on an Orange stripe

Cement service:

Ontinental → ContiTech BM20S BULK MATERIAL DELIVERY WP 20 BAR

Black text on a Yellow stripe

Technical Data:

Part No	Inside Dia		O.D.	Working Pressure		Minimum Burst Pressure		Min Bend Rad	Weight
	mm	Inch	mm	Bar	PSI	Bar	PSI	mm	Kg/M
BM20S-064	102	4	127	20	300	80	1200	612	5.10
BM20S-080	127	5	152	20	300	80	1200	762	6.39

Dunlop Oil & Marine Ltd Jubilee Industrial Estate Ashington, Northumberland NE63 8UB United Kingdom www.dunlop-oil-marine.co.uk



The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2011 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/discl_en